

# MINE STAR - Technical Specifications



## Description

MINE STAR is a bias-ply tire which is an excellent choice for heavy-duty underground mining operations. It features high cut/chip and puncture resistance providing improved operational efficiency. MINE STAR is made of a special compound and features a special tread design resulting in an extended tire life-cycle.

## UM

International Standard

## Construction

 BIAS

## Machinery

OTR: Underground Mining Vehicle

Version	STANDARD
Type	TT
Tyre Size	8.25 - 15

# Dimensions International Standard

Ply Rating	20
Section Width (mm)	244
Overall Diameter (mm)	848
Rim Rec	6.5
Rim Alt	6.0 ; 7.0
Tread Depth	19

## Load capacity (Kg)

km/h / bar	9.30
25	3790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/05/2025 22:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..