

# **TR 459 - Technical Specifications**



#### Description

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

#### UM

US Standard

#### Construction

🐼 BIAS

### Machinery

Agriculture: Backhoe Loader • Tractor Industrial: Backhoe Loader

Version	INDUSTRIAL
Туре	TL
Tyre Size	17.5L - 24
LI/SS	139 A8

## **Dimensions US Standard**

Usa code	94016563
Ply Rating	8
Section Width (inch)	17.5
Overall Diameter (inch)	50
Static Loaded Radius (inch)	21.9
Rolling Circumference (inch)	150.6
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-005212
TRA Code	R4

## Load capacity (lbs)

mph / psi	26
25	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..