

AT 111 - Ficha técnica

Description

AT 111 es idóneo para las aplicaciones deportivas todo terreno con vehículos ATV. Para los usuarios que necesiten una mayor durabilidad, hay disponible una versión "HD" con una banda de rodadura profunda.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Vehículo ATV



SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 18 X 10 - 8	STANDARD	94000845	2	8.0 AT	7.5 AT ; 8.5 AT	10	18	TL	
AT 18 X 10 - 8	STANDARD	94026845	4	8.0 AT	7.5 AT ; 8.5 AT	10	18	TL	E4-75R-0006322
AT 20 X 11 - 8	STANDARD	94000906	6	9.0 AT	8.5 AT	11.1	20	TL	
AT 22 X 11 - 8	STANDARD	94001088	6	9.0 AT	8.5 AT	11.1	22	TL	E4-75R-0004984-01
AT 18 X 10 - 9	STANDARD	94026852	4	8.0 AT	7.5 AT ; 8.5 AT	10	18	TL	E4-75R-0006323
AT 20 X 11 - 9	STANDARD	94000913	4	9.0 AT	8.5 AT	11	20	TL	
AT 20 X 11 - 9	STANDARD	94026876	6	9.0 AT	8.5 AT	11	20	TL	E4-75R-0006326
AT 22 X 11 - 9	STANDARD	94001002	4	9.0 AT	8.5 AT	11.1	22	TL	
AT 22 X 11 - 9	STANDARD	94001095	6	9.0 AT	8.5 AT	11.1	22	TL	E4-75R-0004985-01
AT 18 X 10 - 10	STANDARD	94026906	4	8.0 AT	7.5 AT ; 8.5 AT	10	18	TL	E4-75R-0006324
AT 19 X 6 - 10	STANDARD	94000876	4	5.0		6	18.6	TL	
AT 20 X 11 - 10	STANDARD	94026913	6	9.0 AT	8.5 AT	10.8	20	TL	E4-75R-0006327
AT 20 X 6 - 10	STANDARD	94000937	2	5.0		6	19.7	TL	
AT 20 X 6 - 10	STANDARD	94026920	4	5.0		6	19.7	TL	E4-75R-0006325
AT 21 X 7 - 10	STANDARD	94026937	4	5.5 AT	6.0 AT	7	21.3	TL	E4-75R-0006328
AT 21 X 7 - 10	STANDARD	94026944	6	5.5 AT	6.0 AT	7	21.3	TL	E4-75R-0006329
AT 22 X 11 - 10	STANDARD	94000975	4	9.0 AT	8.5 AT	11.1	22	TL	
AT 22 X 11 - 10	STANDARD	94026951	6	9.0 AT	8.5 AT	11.1	22	TL	E4-75R-0006333
AT 22 X 7 - 10	STANDARD	94026968	4	5.5 AT	6.0 AT	6.9	22	TL	E4-75R-0006330
AT 22 X 7 - 10	STANDARD	94026975	6	5.5 AT	6.0 AT	6.9	22	TL	E4-75R-0006331
AT 22 X 8 - 10	STANDARD	94001101	6	6.5 AT	6.0 AT	8.2	22	TL	E4-75R-0004981-01
AT 23 X 7 - 10	STANDARD	94026982	4	5.5 AT	6.0 AT	7	23	TL	E4-75R-0006334
AT 23 X 7 - 10	STANDARD	94026999	6	5.5 AT	6.0 AT	7	23	TL	E4-75R-0006335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 6:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..