

BK RUF N TUF - Ficha técnica



Description

BK RUF N TUF es un neumático que en la banda de rodadura presenta un dibujo con bloques, idóneo para operaciones de transporte con remolques y camionetas. Es ideal para utilizarlo por carretera y garantiza una óptima duración.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Camión ligero • Remolque

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
7.50 - 16	STANDARD	94014033	8	6.00 G	5.50 F	8.5	32.7	TT	
7.50 - 16	STANDARD	94014040	12	6.00 G	5.50 F	8.5	32.7	TT	
7.50 - 16	STANDARD	94014064	14	6.00 G	5.50 F	8.5	32.7	TT	
7.50 - 16	STANDARD	94014088	16	6.00 G	5.50 F	8.5	32.7	TT	E11-54R-0015401
7.50 - 16	STANDARD	94059133	14	6.00 G	5.50 F	8.5	32.7	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 4:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..