

BOGMAX - Especificaciones técnicas



Description

BOGMAX ha sido particularmente proyectado para las aplicaciones todo terreno. El diseño extra profundo de la banda de rodadura garantiza una excelente tracción mientras que los cordones de protección del flanco reducen los impactos y el riesgo de posibles daños. BOGMAX es un neumático de 6 telas con tecnología M+S – perfecto para el rendimiento deportivo en cualquier condición.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Vehículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 32 X 10 - 14
LI/SS	62 F

Dimensions US Standard

Usa code	94048502
Ply Rating	6
Section Width (inch)	9.8
Overall Diameter (inch)	31.9
Rim Rec	8.0 AT
Rim Alt	8.5 AT

Load capacity (lbs)

mph / psi	7
50	585

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 4:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..