

## D 405 - Especificaciones técnicas



### Description

D 405 es un neumático que se utiliza principalmente en la carretera y es ideal para aplicaciones con remolques y camionetas. El excelente agarre a la superficie de la carretera, junto a un desgaste regular, se traduce en una elevada durabilidad.

### UM

US Standard

### Construction

✚ BIAS

### Machinery

Agricultura: Camión ligero • Remolque

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 7.50 - 16 |

## Dimensions US Standard

|                         |                |
|-------------------------|----------------|
| Usa code                | 94032495       |
| Ply Rating              | 16             |
| Section Width (inch)    | 8.3            |
| Overall Diameter (inch) | 31.9           |
| Rim Rec                 | 6.00 G         |
| Rim Alt                 | 5.50 F         |
| ECE                     | E4-54R-0022812 |

## Load capacity (lbs)

|           |   |
|-----------|---|
| mph / psi | - |
| -         | - |
| -         | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 9:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..