

EARTHMAX SR 43 - Ficha técnica



Description

EARTHMAX SR 43 (L-4) es un neumático radial All Steel particularmente proyectado para palas de ruedas compactas que operan en condiciones rocosas extremas, principalmente en las minas subterráneas. El neumático garantiza excelentes prestaciones en las operaciones de carga y de transporte en las minas a cielo abierto, en las canteras y en las operaciones de demolición. El diseño único de la banda de rodadura asegura una tracción y una estabilidad superiores. Gracias a la estructura All Steel, EARTHMAX SR 43 (L-4) asegura una excelente robustez y resistencia a las laceraciones y los pinchazos, así como un ciclo de vida más largo.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Pala cargadora

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
29.5 R 25	CUT RESISTANT COMPOUND	L4	**	216 A2	25.00/3.5		785	1875	847	5644	TL	61
29.5 R 25	CUT RESISTANT COMPOUND	L4	***	221 A2	25.00/3.5		785	1875	847	5644	TL	61
29.5 R 29	CUT RESISTANT COMPOUND	L4	***	223 A2	25.00/3.5	24.00/3.5, 26.00/3.5	768	2003	905	6029	TL	62
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L4	***	228 A2	27.00/3.5	27.00/3.0; 28.00/3.5	852	1877	844	5702	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	L4	**	224 A2	28.00/3.5		900	2076	957	6412	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	E4/L4	****/***		28.00/3.5		900	2076	957	6412	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	SH4	****		28.00/3.5		900	2076	957	6412	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	L4	***	229 A2	28.00/3.5		900	2076	957	6412	TL	61

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 22:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..