

LG RIB - Ficha técnica



Description

LG RIB es un neumático para el césped y la jardinería, idóneo para segadoras y minitractores. El específico dibujo de la banda de rodadura hace que este neumático sea delicado en el terreno, previniendo daños al prado facilitando al mismo tiempo la manipulación y las maniobras. LG RIB está disponible en una versión "aramid belted", con cinturones de aramida, para usuarios que requieren una mayor resistencia a la perforación.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Segadora • Minitractor

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11 X 4.00 - 5	STANDARD	39 A6	4	3.00 A		104	272			TL	E11-106R-008779
13 X 5.00 - 6	ARAMID BELTED		6	3.50 A		127	325	144	943	TL	E11-106R-005221
13 X 5.00 - 6	STANDARD		4	3.50 A		127	325	144	943	TL	E11-106R-003465
15 X 6.00 - 6	ARAMID BELTED		6	4.50 A		152	365	159	1059	TL	E11-106R-003504
15 X 6.00 - 6	STANDARD		4	4.50 A		152	365	159	1059	TL	E11-106R-003466
15 X 6.00 - 6	STANDARD		6	4.50 A		152	365	159	1059	TL	E4-106R-002173
16 X 6.50 - 8	ARAMID BELTED		10	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-005404
16 X 6.50 - 8	ARAMID BELTED		6	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-003499
16 X 6.50 - 8	STANDARD		8	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	
16 X 6.50 - 8	STANDARD		10	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-003372
16 X 6.50 - 8	STANDARD		4	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TT	E11-106R-003467
16 X 6.50 - 8	STANDARD		4	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-003467
16 X 6.50 - 8	STANDARD		6	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-003468
20 X 10.00 - 10	STANDARD		4	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	236	498	222	1444	TL	E11-106R-003469

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 20:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..