

MAGLIFT - Especificaciones técnicas



Description

MAGLIFT ha sido particularmente proyectado para las operaciones realizadas con las carretillas elevadoras que se usan en las operaciones industriales y en la logística. Este neumático sólido se caracteriza por una elevada capacidad de carga, así como por su excepcional confort. MAGLIFT ofrece una extraordinaria resistencia a cualquier tipo de corte, que se traduce en un ciclo de vida más prolongado para este neumático. La estructura reforzada reduce el riesgo de derrape, mientras que la forma especial del talón facilita su montaje en la llanta.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Carretilla elevadora

Version	LIP
Type	
Tyre Size	250 - 15 (250/70 - 15)

Dimensions US Standard

Usa code	94036936
Section Width (inch)	8.5
Overall Diameter (inch)	28.3
Rim Rec	7.0 - 15

Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	10460
15 STEER WHEEL	8045

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 1:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..