

PAC MASTER - Especificaciones técnicas



Description

PAC MASTER es un neumático diagonal que se utiliza en las máquinas compactadoras. Proporciona una elevada estabilidad y asegura un ciclo de vida prolongado. Este neumático está realizado con una mezcla especial que proporciona una particular resistencia al calor.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	205/60 - 15

Dimensions US Standard

Usa code	94038961
Ply Rating	6
Section Width (inch)	7.9
Overall Diameter (inch)	25.2
Rim Rec	6.0 J
Rim Alt	7.0 J

Load capacity (lbs)

mph / psi	47
5	2340
10	1870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 7:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..