

ROCK GRIP E4 - Especificaciones técnicas



Description

ROCK GRIP (E-4) es un neumático de telas cruzadas especialmente proyectado para los camiones que se utilizan en las minas y las canteras. ROCK GRIP es el neumático ideal cada vez que las condiciones operativas para realizar transportes cortos en el sitio de trabajo requieran tanto resistencia al calor como protección a los cortes.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dúmpers rígidos

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

Dimensions US Standard

Usa code	94041886
Ply Rating	24
Overall Width (inch)	14.8
Overall Diameter (inch)	55.5
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	164.3
Rim Rec	10.00/2.0
TRA Code	E4
Tread Depth	64

Load capacity (lbs)

mph / psi	83
30	11400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 6:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..