

SAND STAR - Especificaciones técnicas



Description

SAND STAR es un neumático con un dibujo de bloques en la banda de rodadura, específicamente desarrollado para los remolques. Asegura una excelente tracción en las superficies arenosas y un óptimo contacto con el terreno, reduciendo también la compactación del suelo.

UM

US Standard

Construction

✚ BIAS

Machinery

Industrial: Remolque

Version	STANDARD
Type	TT
Tyre Size	9.00 - 13
LI/SS	108 D

Dimensions US Standard

Usa code	94031047
Ply Rating	6
Section Width (inch)	9.6
Overall Diameter (inch)	30.9
Rim Rec	5.50 F
Rim Alt	5.50 WB
ECE	E11-106R-005296

Load capacity (lbs)

mph / psi	45
40	2205

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 5:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..