

## SM 55 IND-5S - Ficha técnica



### Description

SM 55 IND-5S ha sido específicamente proyectado para las grúas **reach stacker** y las máquinas para la manipulación de contenedores. La mezcla especial de la banda de rodadura, resistente a la abrasión, asegura una larga vida del neumático sobre las superficies asfaltadas o cementadas y ofrece una excelente estabilidad a los vehículos en modalidad de levantamiento.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Manipulador de contenedores

| SIZE       | Version         | TRA Code | PR | RIM REC   | RIM ALT                      | OW  | OD   | SLR | RC   | Type |
|------------|-----------------|----------|----|-----------|------------------------------|-----|------|-----|------|------|
| 12.00 - 24 | PORT INDUSTRIAL | IND5     | 20 | 8.5       | 7.33 V ; 8 ; 8.00 V ; 8.50 V | 310 | 1275 | 594 | 3777 | TT   |
| 18.00 - 25 | PORT SPECIAL    | IND5     | 40 | 13.00/2.5 | 15.00/2.5                    | 517 | 1665 | 765 | 5118 | TL   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 22:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..