

## TR 273 - Ficha técnica



### Description

TR 273 es un neumático para tractores, idóneo para utilizarlo en las labores del campo. Este neumático ha sido especialmente proyectado para ofrecer máximas prestaciones en terrenos húmedos y mojados. En estas condiciones del terreno, a un neumático se le requiere que ofrezca un agarre superior, así como elevadas propiedades de auto limpieza. TR 273 satisface perfectamente todas estas características.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor

| SIZE      | Version  | USACode  | TRA Code | LI/SS  | PR | RIM REC           | RIM ALT         | SW   | OD   | SLR  | RC    | Type | TMPH | ECE             |
|-----------|----------|----------|----------|--------|----|-------------------|-----------------|------|------|------|-------|------|------|-----------------|
| 12.4 - 24 | STANDARD | 94054114 | R2       | 117 A8 | 8  | W 11              | W 10            | 12.4 | 47   | 21.7 | 146.5 | TT   | 0    | E11-106R-004100 |
| 13.6 - 24 | STANDARD | 94057450 | R2       | 120 A8 | 8  | W 12              | W 11            | 13.8 | 48.8 | 22.4 | 149.4 | TT   | 1    | E11-106R-005252 |
| 14.9 - 24 | STANDARD | 94051410 | R2       | 124 A8 | 8  | W 13              | W 12            | 15   | 51.6 | 23.4 | 159.2 | TT   | 0    | E11-106R-004514 |
| 14.9 - 24 | STANDARD | 94051427 | R2       | 128 A8 | 10 | W 13              | W 12            | 15   | 51.6 | 23.4 | 159.2 | TT   | 0    | E11-106R-004515 |
| 18.4 - 26 | STANDARD | 94057283 | R2       | 142 A8 | 12 | W 16              | W 15            | 18.5 | 58.7 | 26.5 | 178.5 | TT   | 1    | E11-106R-005314 |
| 23.1 - 26 | STANDARD | 94055425 | R2       | 152 A6 | 14 | DW 20 A ; DW 20 B |                 | 23.2 | 65.2 | 29   | 198.9 | TT   | 0    | E11-106R-004628 |
| 23.1 - 26 | STANDARD | 94039784 | R2       | 145 A8 | 10 | DW 20 A ; DW 20 B |                 | 23.2 | 65.2 | 29   | 198.9 | TT   | 0    | E11-106R-003620 |
| 23.1 - 26 | STANDARD | 94039821 | R2       | 149 A8 | 12 | DW 20 A ; DW 20 B |                 | 23.2 | 65.2 | 29   | 198.9 | TT   | 0    | E11-106R-003395 |
| 14.9 - 28 | STANDARD | 94054121 | R2       | 126 A8 | 8  | W 13              | W 12            | 15.2 | 55.5 | 25.6 | 172   | TT   | 0    | E11-106R-004516 |
| 16.9 - 30 | STANDARD | 94057238 | R2       | 140 A8 | 12 | W 15 L            | W 14 L          | 17.1 | 60.2 | 27.8 | 189   | TT   | 1    | E11-106R-005315 |
| 18.4 - 30 | STANDARD | 94042418 | R2       | 145 A8 | 12 | W 16 L            | W 15 L          | 18.3 | 62.4 | 28.5 | 193.9 | TT   | 0    | E11-106R-003621 |
| 23.1 - 30 | STANDARD | 94045716 | R2       | 147 A8 | 10 | DW 20 A ; DW 20 B |                 | 23.2 | 68.8 | 31.3 | 210.9 | TT   | 0    | E11-106R-003622 |
| 23.1 - 30 | STANDARD | 94045693 | R2       | 154 A8 | 14 | DW 20 A ; DW 20 B |                 | 23.2 | 68.8 | 31.3 | 210.9 | TT   | 0    | E11-106R-003645 |
| 18.4 - 34 | STANDARD | 94055821 | R2       | 146 A8 | 12 | DW 16A            | W16L,W15L,DW15L | 18.7 | 67   | 30.5 | 206.8 | TT   | 0    | E11-106R-004517 |
| 23.1 - 34 | STANDARD | 94045730 | R2       | 150 A8 | 10 | DW 20 A ; DW 20 B |                 | 23.2 | 72.8 | 32.8 | 221.8 | TT   | 0    | E11-106R-003623 |
| 23.1 - 34 | STANDARD | 94045907 | R2       | 157 A8 | 14 | DW 20 A ; DW 20 B |                 | 23.2 | 72.8 | 32.7 | 223.4 | TT   | 1    | E11-106R-003646 |
| 18.4 - 38 | STANDARD | 94056590 | R2       | 149 A8 | 12 | W 16              | W 15            | 18.3 | 70.9 | 32.4 | 219.6 | TT   | 1    | E11-106R-005316 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 4:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The

user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..