

XL GRIP IND3 (ECH) - Especificaciones técnicas



Description

XL GRIP (IND-3) es un neumático de telas cruzadas que se utiliza en los equipos de manipulación de los contenedores vacíos en las aplicaciones de apilado y elevación. Este neumático se caracteriza por una robusta carcasa que asegura una durabilidad avanzada, así como una elevada estabilidad en la modalidad de levantamiento.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Manipulador de contenedores vacios

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94032785
Ply Rating	24
Overall Width (inch)	12.6
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	146.1
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND3

Load capacity (lbs)

mph / psi	145
5	22650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 3:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..