

FL 695 - Technical Specifications



Description

FL 695 has been specifically designed for trailers in construction and transport applications with a unique center block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions and its deep tread ensures optimal self-cleaning during on and off-road applications. Multiple steel cord layers reinforce this pattern against punctures.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Trailer

Industrial: Trailer

Version	STEEL BELTED
Type	TL
Tyre Size	600/60 R 30.5
LI/SS	179 D
LI/SS DRIVE WHEEL	179 D
LI/SS FREE ROLLING	179 D

Dimensions US Standard

Usa code	94073832
Section Width (inch)	24.1
Overall Diameter (inch)	58.9
Static Loaded Radius (inch)	27.3
Rolling Circumference (inch)	180.6
Rim Rec	AG20.00
ECE	E11-106R-008503

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	65	73	80	87
40	--	--	--	7690	8880	10090	11110	12140	13330	14190	15030	16060	17080
30	--	--	--	9310	10760	12200	13450	14680	16140	17170	18200	19440	20680
25	--	7670	9530	10460	12090	13710	15110	16500	18130	19290	2060	21850	23240
20	6460	8520	10580	11620	13430	15230	16780	18330	20130	21430	22720	24260	25800
15	6760	8920	11080	12160	14040	15930	17550	19170	21060	22410	23760	25380	26990
10	7050	9310	11560	12700	14670	16640	18330	20030	22000	23410	24820	26510	28200
5	7690	10150	12610	13840	15990	17280	18150	19990	21840	24000	27070	28910	30750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 21:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..