

## FLOTATION 351 - Data Sheet

### Description

FLOTATION 351 is a bias flotation tire which best suits transport applications using trailers. Extra deep lugs provide outstanding traction and a longer tire life. FLOTATION 351 is the ideal tire on wet and moist surfaces ensuring high load capacity.

### UM

US Standard

### Construction

✚ BIAS

### Machinery

Agriculture: Trailer



SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
42 X 25.00 - 20	STANDARD	94006595	HF3	135 B	12	20.50 HF	20.50 VF	23.8	43.7	20	130	TL	E11-106R-004382
42 X 25.00 - 20	STANDARD	94033652	HF3	139 B	16	20.50 HF	20.50 VF	23.8	43.7	20	130	TL	E11-106R-004383
48 X 25.00 - 20	STANDARD	94025657	HF3	144 B	10	20.50 HF	20.50 VF	24.8	50	22	149	TL	
48 X 31.00 - 20	STANDARD	94026135	HF3	148 B	12	26.00 HF	26.00 VF	30.5	50.5	22	153	TL	E11-106R-004385
66 X 43.00 - 25	STANDARD	94029495	HF3	170 B	16	36.0 TH		40.2	68.9	30.8	205.2	TL	E11-106R-003346
66 X 43.00 - 25	STANDARD	94042999	HF3	150 B	6	36.0 TH		40.2	68.9	30.8	205.2	TL	
66 X 43.00 - 25	STANDARD	94029327	HF3	160 B	10	36.0 TH		40.2	68.9	30.8	205.2	TL	E11-106R-004378

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 20:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..