

AGRIMAX TURF RT 333 - Spécifications techniques



Description

AGRIMAX TURF RT 333 (R-3+) est un pneu radial conçu pour les petits tracteurs utilisés dans le jardinage, les vignobles et les vergers. Sa conception à épaulement arrondi permet un faible compactage du sol et le rend extrêmement délicat sur le terrain. Sa bande de roulement extra-profonde (R-3+) et sa conception spéciale à blocs directionnels lui assurent une excellente traction dans les champs et sur la route, ainsi qu'une durée de vie prolongée du pneu. AGRIMAX TURF RT 333 (R-3+) dispose de grandes propriétés autonettoyantes et permet, grâce à sa faible résistance au roulement, de réaliser d'importantes économies de carburant.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur pour vergers • Micro tracteur •
Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	480/70 R 28
LI/SS	140 A8 / 140 B

Dimensions US Standard

Usa code	94075393
Section Width (inch)	18.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	166.5
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-009049

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3040	3530	4030	4520	5020	5520
25	3040	3530	4030	4520	5020	5520
20	3260	3790	4310	4840	5370	5900
5 LT	4070	4730	5410	6070	6730	7390
5 HT	3260	3790	4310	4840	5370	5900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 23:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..