

AS 511 - Fiche de données



Description

AS 511 est parfaitement adapté pour les outils agricoles dans les applications sur pelouses. La carcasse robuste et le mélange de la bande de roulement particulièrement résistant aux coupures et déchirures assurent une stabilité exceptionnelle et des performances accrues. Grâce à la large zone de contact, AS 511 fournit une excellente traction et minimise le compactage du sol.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Outillage agricole

SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
31 X 15.50 R 15	STANDARD	94059782	13 LB		15.3	30.9	13.9	94	TL	E11-106R-005098
33 X 15.50 R 15	STANDARD	94512379	13 LB		15.9	33.1	14.8	99.7	TL	E11-106R-0010516

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 21:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..