

AW 705 - Spécifications techniques



Description

AW 705 a été conçu pour les outils agricoles et remorques dans les applications de travail de la terre et de transport. Il convient pour être utilisé dans l'agriculture moderne grâce à une durabilité supérieure et une capacité de charge élevée.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	138 A8

Dimensions US Standard

Usa code	94010028
Ply Rating	12
Section Width (inch)	15
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	101.4
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-001549

Load capacity (lbs)

mph / psi	45
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 23:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..