

AW 729 - Fiche de données



Description

L'AW 729 est un pneu agricole spécialement conçu pour le transport, la récolte du foin, le bottelage et le travail des sols. Son épaulement arrondi et la conception de sa bande de roulement à trois rainures centrales assurent un faible compactage du sol et évitent les dégâts causés au champ. L'AW 729 est le pneu idéal pour l'agriculture moderne. Il est adapté pour une utilisation aussi bien sur route que hors route.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
340/55 - 16 (13.0/55 - 16)	STANDARD	121 A8	133 A8		11.0		343	785	358	2358	TL	E11-106R-006421
15.0/55 - 17	STANDARD	122 A8	134 A8	10	13.00	13 ; W 13	385	850	377	2560	TL	E11-106R-006434
380/55 - 17	STANDARD	122 A8	134 A8	10	13.00	13 ; W 13	385	850	377	2560	TL	E11-106R-008727
480/45 - 17	STANDARD	134 A8	146 A8		16.00		480	866	400	2526	TL	E11-106R-006798
500/50 - 17	STANDARD	137 A8	149 A8		16.00		500	945	426	2885	TL	E11-106R-006616

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 08:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..