

EARTHMAX SR 43 - Fiche de données



Description

Earthmax SR 43 (L-4) est un pneu radial All Steel particulièrement conçu pour les chargeuses sur pneus qui opèrent dans des conditions rocheuses extrêmes, notamment dans les mines souterraines. Ce pneu garantit d'excellentes performances pour les opérations de chargement et de transport dans les mines à ciel ouvert, les carrières et les chantiers de démolition. Le dessin unique de la bande de roulement assure de meilleures traction et stabilité. Grâce à sa structure All Steel, Earthmax SR 43 (L-4) bénéficie d'une solidité optimale et d'une excellente résistance aux déchirures et crevaisons ainsi que d'un cycle de vie plus long.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Chargeur

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
29.5 R 25	CUT RESISTANT COMPOUND	L4	**	216 A2	25.00/3.5		785	1875	847	5644	TL	61
29.5 R 25	CUT RESISTANT COMPOUND	L4	***	221 A2	25.00/3.5		785	1875	847	5644	TL	61
29.5 R 29	CUT RESISTANT COMPOUND	L4	***	223 A2	25.00/3.5	24.00/3.5, 26.00/3.5	768	2003	905	6029	TL	62
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L4	***	228 A2	27.00/3.5	27.00/3.0; 28.00/3.5	852	1877	844	5702	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	L4	**	224 A2	28.00/3.5		900	2076	957	6412	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	E4/L4	****/***		28.00/3.5		900	2076	957	6412	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	SH4	****		28.00/3.5		900	2076	957	6412	TL	61
35/65 R 33	CUT RESISTANT COMPOUND	L4	***	229 A2	28.00/3.5		900	2076	957	6412	TL	61

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 03:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..