

FARM SPECIAL - Fiche de données



Description

FARM SPECIAL est un pneu pour tracteurs approprié pour les opérations de travail de la terre. La carcasse robuste garantit un haut niveau de résistance aux crevaisons et un cycle de vie plus long, tandis que les épaules arrondies évitent d'endommager le sol et protègent donc les précieuses cultures. FARM SPECIAL se distingue de par le dessin unique de sa bande de roulement avec des éléments mud breaker (briseurs de boue) qui optimisent les propriétés d'auto nettoyage. De plus, l'angle à double orientation des revés assure une excellente traction avec un moindre glissement.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
11.2 - 24	STANDARD	94060795	R1	112 A8	8	W 10	W 9	11.2	43.1	20	129.3	TT	0	E11-106R-005528
12.4 - 24	STANDARD	94060696	R1	118 A8	8	W 11	W 9 ; W 10	12.6	45.5	21	138	TT	0	E11-106R-005529
13.6 - 24	STANDARD	94060702	R1	120 A8	8	W 12	W 11	13.8	47.4	21.8	143.1	TT	0	E11-106R-005530
14.9 - 24	STANDARD	94060719	R1	124 A8	8	W 13	W 11 ; W 12	14.9	49.4	22.5	148.6	TT	0	E11-106R-005531
9.5 - 24	STANDARD	94060689	R1	108 A8	8	W 8	W 7	9.4	41.3	19.3	125.7	TT	0	E11-106R-005527
11.2 - 28	STANDARD	94060337	R1	114 A8	8	W 10	W 9	11.2	47.4	22.2	145.4	TT	0	E11-106R-005532
12.4 - 28	STANDARD	94060726	R1	120 A8	8	W 11	W 9 ; W 10	12.4	49.8	23.2	151.7	TT	0	E11-106R-005533
13.6 - 28	STANDARD	94060801	R1	122 A8	8	W 12	W 11	13.8	51.6	24	156.9	TT	0	E11-106R-005534
14.9 - 28	STANDARD	94060818	R1	126 A8	8	W 13	W 11 ; W 12	14.8	53.3	24.4	161.6	TT	0	E11-106R-005535
16.9 - 30	STANDARD	94061976	R1	132 A8	8	W 15 L	W 14 L	17	57.8	26.4	175.4	TT	0	E11-106R-005536
18.4 - 30	STANDARD	94061983	R1	135 A8	8	W 16 L	W 15 L	17.8	60.4	27.1	181.1	TT	0	E11-106R-005537
12.4 - 32	STANDARD	94060849	R1	121 A8	8	W 11	W 9 ; W 10	12.6	53.5	25	162.9	TT	0	E11-106R-005538
13.6 - 36	STANDARD	94061747	R1	125 A8	8	W 12	W 11	13.6	59.6	27.7	180.7	TT	0	E11-106R-005539
13.6 - 38 (14.00 - 38)	STANDARD	94058693	R1	127 A8	8	W 12	W 11	13.6	61.6	29	191.9	TT	1	E11-106R-005540
14.00 - 38 (13.6 - 38)	STANDARD	94053582	R1	127 A8	8	W 12	W 11	13.6	61.6	29	191.9	TT	0	E11-106R-004381
15.5 - 38	STANDARD	94060344	R1	129 A8	8	W 14 L		15.5	62	28.8	189.5	TT	0	E11-106R-005541

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 23:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..