

FLOTATION 648 - Spécifications techniques



Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	550/45 - 22.5
LI/SS DRIVE WHEEL	147 A8/144 B
LI/SS FREE ROLLING	159 A8/156 B

Dimensions US Standard

Usa code	94006366
Ply Rating	16
Section Width (inch)	20.7
Overall Diameter (inch)	42.1
Static Loaded Radius (inch)	19.2
Rolling Circumference (inch)	128.1
Rim Rec	AG 16.00
ECE	E4-106R-002309

Load capacity (lbs)

mph / psi	35	38	41
5 FR	12350	12930	13500
10 FR	11110	11640	12160
20 FR	9880	10350	10800
25 FR	8820	9240	9640
30 FR	7940	8310	8820
5 DW	8670	9090	9490
10 DW	7800	8180	8540
20 DW	6930	7270	7590
25 DW	6190	6490	6780
30 DW	5580	5840	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 02:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..