

GIANT TRAX - Fiche de données



Description

GIANT TRAX a été conçu pour les chargeuses compactes qui opèrent sur les surfaces rugueuses que l'on trouve dans les parcs à ferraille et pour les applications de recyclage et minières. La bande de roulement extra profonde aux blocs plus larges et plus robustes assure d'excellentes qualités de traction, stabilité et résistance aux perforations. Le mélange spécial de la bande de roulement confère une extraordinaire résistance aux coupures et déchirures, ainsi qu'une excellente résistance à l'usure sur tout type de terrain.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur compact

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	IMPLEMENT	123 A8	12	8.25		270	775	362	2317	TL	E11-106R-003579
10 - 16.5	STANDARD		12	8.25		270	775	362	2317	TL	E11-106R-003579
12 - 16.5	STANDARD		14	9.75		315	840	398	2521	TL	E11-106R-005562
14 - 17.5	STANDARD	155 A2	14	10.50		350	915	421	2714	TL	E11-106R-006019

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 04:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..