

INDUSTRIAL RIB F3 - Spécifications techniques



Description

INDUSTRIAL RIB F3 est un pneu agro-industriel avec dessin à blocs de la bande de roulement conçu pour le transport aux champs et sur route ainsi que pour les travaux des champs avec outils agricoles et remorques. Ce pneu se distingue de par son mélange extrêmement résistant aux chaumes qui le rend idéal pour les conditions de fonctionnement les plus critiques, et lui assure un long cycle de vie.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Outillage agricole • Remorque

Version	SPECIAL
Type	TL
Tyre Size	11L - 16 SL
LI/SS	116 A6

Dimensions US Standard

Usa code	94028689
Ply Rating	10
Section Width (inch)	11
Overall Diameter (inch)	32.7
Rim Rec	W 8 L
Rim Alt	8 LB ; 10 LB ; W 10 L
ECE	E11-106R-004304
TRA Code	F3

Load capacity (lbs)

mph / psi	52
20	2760
25	2470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 03:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..