

## MP 600 - Fiche de données



### Description

MP 600 est un pneu agro-industriel pour le secteur entretien de la voirie avec les chargeurs télescopiques et les outils agricoles en assurant une expérience de conduite confortable. Ce pneu offre une traction et des qualités d'autonettoyage excellentes en même temps qu'un long cycle de vie.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Outillage agricole • Chargeuse télescopique  
Industriel: Chargeuse télescopique • Véhicule universel

| SIZE                          | Version  | USACode  | LI/SS DRIVE WHEEL | PR | RIM REC | RIM ALT | SW   | OD   | SLR  | RC    | Type | ECE             |
|-------------------------------|----------|----------|-------------------|----|---------|---------|------|------|------|-------|------|-----------------|
| 10.5 - 18                     | STANDARD | 94015290 |                   | 10 | 9       | 9 SDC   | 10.7 | 36.2 | 16.5 | 107.9 | TL   | E11-106R-003581 |
| 12.5 - 18                     | STANDARD | 94015306 |                   | 10 | 11      | 12 SDC  | 12.1 | 39   | 17.7 | 116.1 | TL   |                 |
| 12.5 - 18                     | STANDARD | 94015313 |                   | 12 | 11      | 12 SDC  | 12.1 | 39   | 17.7 | 116.1 | TL   |                 |
| 400/70 - 20<br>(16.0/70 - 20) | STANDARD | 94048403 |                   | 14 | 13 SDC  | 12      | 15.9 | 42.7 | 0    | 0     | TL   |                 |
| 400/70 - 24<br>(16.0/70 - 24) | SPECIAL  | 94051618 |                   | 14 | 13 SDC  | 12      | 15.9 | 46.7 | 21.5 | 139   | TL   |                 |
| 400/70 - 24<br>(16.0/70 - 24) | STANDARD | 94015320 |                   | 14 | 13 SDC  | 12      | 15.9 | 46.7 | 21.5 | 139   | TL   | E11-106R-003640 |
| 400/70 - 24<br>(16.0/70 - 24) | STANDARD | 94042043 |                   | 10 | 13 SDC  | 12      | 15.9 | 46.7 | 21.5 | 139   | TL   |                 |
| 400/70 - 24<br>(16.0/70 - 24) | STANDARD | 94049318 | 158 A8            | 18 | 13 SDC  | 12      | 15.9 | 46.7 | 21.5 | 139   | TL   | E11-106R-003641 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/05/2025 16:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..