

RIDEMAX IT 696 - Spécifications techniques



Description

RIDEMAX IT 696 est caractérisé par un dessin unique de la bande de roulement et une empreinte large qui lui confère une excellente adhérence pour les applications sur route même en hiver. Le pneu convient parfaitement aux applications de transport et de service voirie des municipalités, grâce également à ses caractéristiques de grande vitesse et à la carcasse robuste. Le dessin de la bande de roulement a été particulièrement développé pour le service lourd et il assure une faible résistance au roulement, ce qui se traduit par des économies de carburant en plus d'une grande stabilité.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	240/70 R 16 IND
LI/SS	107A8/107B

Dimensions US Standard

Usa code	94067503
Section Width (inch)	9.6
Overall Diameter (inch)	29.2
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	87.6
Rim Rec	W8
Rim Alt	W9
ECE	E11-106R-006942

Load capacity (lbs)

mph / psi	17	23	29	35	41
30	1200	1490	1610	1900	2150
25	1200	1490	1610	1900	2150
20	1290	1600	1730	2170	2300
10	1490	1840	1980	2500	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 06:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..