

RIDEMAX IT 696 - Spécifications techniques



Description

RIDEMAX IT 696 est caractérisé par un dessin unique de la bande de roulement et une empreinte large qui lui confère une excellente adhérence pour les applications sur route même en hiver. Le pneu convient parfaitement aux applications de transport et de service voirie des municipalités, grâce également à ses caractéristiques de grande vitesse et à la carcasse robuste. Le dessin de la bande de roulement a été particulièrement développé pour le service lourd et il assure une faible résistance au roulement, ce qui se traduit par des économies de carburant en plus d'une grande stabilité.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	420/65 R 24 IND
LI/SS	146 D/151 A8

Dimensions US Standard

Usa code	94058464
TMPH	1
Section Width (inch)	16.5
Overall Diameter (inch)	45.6
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	137.1
Rim Rec	DW 13 L; W13
Rim Alt	DW 15 L ; DW 14 L
ECE	E11-106R-005952

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58
40	2650	3240	3640	4300	4890	5490	6020	6610
30	2850	3510	3920	4640	5290	5930	6500	7140
25	3040	3730	4190	4950	5630	6320	6920	7610
20	3170	3890	4360	5160	5870	6590	7220	7940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 22:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..