

## ROCK GRIP IND4 (ECH) - Spécifications techniques



### Description

Le ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) est un pneu à carcasse diagonale conçu pour chariots de conteneurs vides dans plusieurs applications, notamment la manutention industrielle et les aciéries. Le composé spécial ROCK GRIP garantit une résistance particulière à la chaleur ainsi qu'une stabilité et une durabilité optimales

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Chariot porte-conteneurs vide

|           |                 |
|-----------|-----------------|
| Version   | PORT INDUSTRIAL |
| Type      | TT              |
| Tyre Size | 12.00 - 24      |

## Dimensions US Standard

|                              |          |
|------------------------------|----------|
| Usa code                     | 94047413 |
| Ply Rating                   | 24       |
| Overall Width (inch)         | 12.4     |
| Overall Diameter (inch)      | 49.8     |
| Static Loaded Radius (inch)  | 23.4     |
| Rolling Circumference (inch) | 147.8    |
| Rim Rec                      | 8.5      |
| Rim Alt                      | 8.0      |
| TRA Code                     | IND4     |

## Load capacity (lbs)

|           |       |
|-----------|-------|
| mph / psi | 145   |
| 5         | 22640 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 07:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..