

ROCK STAR L4 - Spécifications techniques



Description

ROCK STAR LOADER a été particulièrement conçu pour les grues et les chargeurs. En plus d'une excellente traction, le mélange unique de la bande de roulement est particulièrement résistant aux coupures et déchirures. ROCK STAR LOADER est un pneu à 24 plis pour une capacité de charge élevée alors que longévité.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur

Version	STANDARD
Type	TT
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	24
TKPH	1
Overall Width (mm)	390
Overall Diameter (mm)	1425
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	L4

Load capacity (Kg)

km/h / bar	8.50
10	9500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 01:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..