

## RT 857 - Spécifications techniques



### Description

RT 857 est un pneu qui convient pour les applications de travail de la terre. La carcasse robuste garantit une durabilité et une traction excellentes. Le mélange de la bande de roulement est caractérisé par une résistance élevée à tout type de coupure.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tracteur

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 420/85 R 26<br>(16.9 R 26) |
| LI/SS     | 138 A8/B                   |

## Dimensions US Standard

|                              |                                    |
|------------------------------|------------------------------------|
| Usa code                     | 94045013                           |
| Section Width (inch)         | 17.7                               |
| Overall Diameter (inch)      | 54.1                               |
| Static Loaded Radius (inch)  | 24.3                               |
| Rolling Circumference (inch) | 162                                |
| Rim Rec                      | DW 15 L                            |
| Rim Alt                      | W 14 L ; W 15 L ; W 16 L ; DW 16 L |
| ECE                          | E11-106R-003471                    |
| TRA Code                     | R1                                 |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 2870 | 3340 | 3800 | 4280 | 4740 | 5200 |
| 25        | 2870 | 3340 | 3800 | 4280 | 4740 | 5200 |
| 20        | 3080 | 3570 | 4080 | 4570 | 5080 | 5580 |
| 5 LT      | 3850 | 4480 | 5100 | 5730 | 6360 | 6980 |
| 5 HT      | 3080 | 3570 | 4080 | 4570 | 5080 | 5580 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 23:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..