

SKID POWER HD (A) - Spécifications techniques



Description

SKID POWER HD (A) a été conçu pour les chargeuses compactes dans les applications de bâtiment. Ce pneu se distingue de par la bande de roulement extra profonde et la protection des flancs, qui lui confèrent une excellente résistance aux coupures et déchirures ainsi qu'une extraordinaire durabilité. SKID POWER HD (A) est le pneu idéal pour les surfaces terreuses et les conditions pénibles.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	15 - 19.5

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	1019
Static Loaded Radius (mm)	463
Rolling Circumference (mm)	3075
Rim Rec	11.75
Rim Alt	12.25

Load capacity (Kg)

km/h / bar	4.85
10	4565
15	3605
25	3330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 05:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..