

SM 55 L5S - Fiche de données



Description

SM 55 (L-5S) est un pneu à construction diagonale idéal pour les opérations souterraines dans les mines. La bande de roulement est réalisée dans un mélange spécial résistant aux coupures et déchirures, et est caractérisée par une profondeur extra L-5S. Ceci se traduit par des temps d'arrêt machine réduits, assurant ainsi une plus longue vie du pneu. Ce pneu est aussi disponible en version "steel belted" avec ceintures en acier.

UM

US Standard

Construction

✚ BIAS

Machinery

OTR: Tombereau surbaissé • Véhicule miniers souterrains

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
7.00 - 12	DUAL BEAD	94058716	L5S	16	5.00 S		8.1	28	12.7	85	TT	39
7.00 - 12	STANDARD	94044986	L5S	14	5.00 S		8.1	28	12.7	85	TT	39
7.00 - 12	STANDARD	94046058	L5S	16	5.00 S		8.1	28	12.7	85	TT	39
9.50 - 20	STANDARD	94061853	L5S	16	7.5		10.8	41.9	19.9	129.1	TT	72
12.00 - 24	STANDARD	94030873	L5S	20	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	12.2	50.2	23.4	148.7	TT	76
12.00 - 24	STANDARD	94030835	L5S	24	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	12.2	50.2	23.4	148.7	TT	76
12.00 - 24	STEEL BELTED	94035984	L5S	24	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	12.2	50.2	23.4	148.7	TT	76
17.5 - 25	ARASHIELD	94052974	L5S	24	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	17.2	54.1	24.8	159.2	TL	80
17.5 - 25	STANDARD	94030651	L5S	24	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	17.2	54.1	24.8	159.2	TL	80
17.5 - 25	STANDARD	94025886	L5S	20	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	17.2	54.1	24.8	159.2	TL	80
17.5 - 25	STEEL BELTED	94040216	L5S	20	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	17.2	54.1	24.8	159.2	TL	80
17.5 - 25	STEEL BELTED	94040568	L5S	24	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	17.2	54.1	24.8	159.2	TL	80
18.00 - 25	ARASHIELD	94052981	L5S	40	13.00/2.5	15.00/2.5	20.4	65.6	30.1	201.5	TL	105
18.00 - 25	STANDARD	94026807	L5S	28	13.00/2.5	15.00/2.5	20.4	65.6	30.1	201.5	TL	105
18.00 - 25	STANDARD	94025718	L5S	40	13.00/2.5	15.00/2.5	20.4	65.6	30.1	201.5	TL	105
18.00 - 25	STANDARD	94053230	L5S	32	13.00/2.5	15.00/2.5	20.4	65.6	30.1	201.5	TL	105
18.00 - 25	STEEL BELTED	94040223	L5S	28	13.00/2.5	15.00/2.5	20.4	65.6	30.1	201.5	TL	105
18.00 - 25	STEEL BELTED	94044696	L5S	40	13.00/2.5	15.00/2.5	20.4	65.6	30.1	201.5	TL	105
20.5 - 25	STANDARD	94069859	L5S	20	17.00/2.0		20.9	61.6	0	0	TL	101
26.5 - 25	ARASHIELD	94052998	L5S	36	22.00/3.0		27.6	70.8	32.1	209.5	TL	121
26.5 - 25	STEEL BELTED	94039951	L5S	28	22.00/3.0		27.6	70.8	32.1	209.5	TL	121
26.5 - 25	STEEL BELTED	94045488	L5S	32	22.00/3.0		27.6	70.8	32.1	209.5	TL	121
29.5 - 29	ARASHIELD	94064267	L5S	40	25.00/3.5	24.00/3.5	29.7	79.5	34.7	237	TL	131
29.5 - 29	STEEL BELTED	94058242	L5S	40	25.00/3.5	24.00/3.5	29.7	79.5	34.7	237	TL	131
29.5 - 29	STEEL BELTED	94040407	L5S	28	25.00/3.5	24.00/3.5	29.7	79.5	34.7	237	TL	131
35/65 - 33	ARASHIELD	94063864	L5S	48	28.00/3.5		36.2	82.1	0	0	TL	123
35/65 - 33	STEEL BELTED	94060931	L5S	48	28.00/3.5		36.2	82.1	0	0	TL	123
45/65 - 45	STEEL BELTED	94058730	L5S	58	36.00/4.5		45.1	108.3	0	0	TL	146

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 01:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..