



GF 304 - Data Sheet



Description

GF 304 is suitable for golf applications with golf carts. GF 304 ensures best comfort and turf protection. GF 304 is also available as "aramid-belted" version to provide increased puncture resistance.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Golf Kart

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	ARAMID BELTED	94008056	4	7.00 I - 55 ; I - 70 ; I - 90		8.5	18.1	8	52.5	TL	E11-106R-005218
18 X 8.50 - 8	STANDARD	94008049	4	7.00 I - 55 ; I - 70 ; I - 90		8.5	18.1	8	52.5	TL	E11-106R-003442
18 X 8.50 - 8	STANDARD	94031078	6	7.00 I - 55 ; I - 70 ; I - 90		8.5	18.1	8	52.5	TL	E11-106R-005197

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 17:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..