

GIANT TRAX - Technical Specifications



Description

GIANT TRAX has been designed for skid steer loaders in scrap yard operations, on rough concrete surfaces, recycling applications and mines. The extra deep tread with wider and sturdier blocks provides best traction, stability, and puncture resistance. The special tread compound results in exceptional cut and chip resistance along with excellent wear resistance on all types of terrains.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Skid Steer

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 14 - 17.5 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94064403 |
| Ply Rating | 14 |
| Section Width (inch) | 13.8 |
| Overall Diameter (inch) | 36 |
| Static Loaded Radius (inch) | 16.6 |
| Rolling Circumference (inch) | 106.9 |
| Rim Rec | 10.50 |
| ECE | E11-106R-006019 |

Load capacity (lbs)

| mph / psi | 80 |
|-----------|------|
| 5 | 8540 |
| 10 | 6750 |
| 15 | 6240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 23:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..