

AGRIMAX ELOS - Specifiche tecniche



Description

AGRIMAX ELOS è stato progettato per esprimere la massima trazione anche in condizioni d'uso particolarmente problematiche su terreni bagnati – ad esempio risaie – e paludosi. Il disegno del battistrada è stato specificatamente studiato per garantire ottime qualità di autopulitura, un aspetto essenziale nei lavori sui campi fangosi e durante i trasferimenti. Per ottimizzare la produttività dell'azienda agricola, nel design dello pneumatico Agrimax Elos sono stati integrati dei cordoli di protezione sui fianchi per assicurare in ogni momento la massima protezione da possibili danneggiamenti.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	380/85 R 38 (14.9 R 38)
LI/SS	139 A8/B

Dimensions US Standard

Usa code	94036134
Section Width (inch)	15
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	30.4
Rolling Circumference (inch)	196.6
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-000779
TRA Code	R2

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2950	3440	3910	4400	4880	5360
25	2950	3440	3910	4400	4880	5360
20	3160	3680	4200	4720	5240	5740
5 LT	3960	4610	5250	5900	6550	7190
5 HT	3160	3680	4200	4720	5240	5740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..