

AGRIMAX SPARGO - Specifiche tecniche



Description

AGRIMAX SPARGO è lo pneumatico BKT specifico per applicazioni nelle colture in filari, progettato per aumentare la produttività del campo conservando il suolo nel lungo termine. Dotato di tecnologia VF, lo pneumatico offre una maggiore capacità di carico con gonfiaggio standard. Grazie alla carcassa robusta e il maggior numero di ramponi, AGRIMAX SPARGO garantisce eccellente durabilità abbinata ad una forte stabilità sia sul campo che durante gli spostamenti su strada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	VF 380/90 R 46
LI/SS	175 D

Dimensions US Standard

Usa code	94070206
Section Width (inch)	15.4
Overall Diameter (inch)	72.9
Static Loaded Radius (inch)	33.4
Rolling Circumference (inch)	219.8
Rim Rec	DW 13 A
Rim Alt	W 13 A ; DW 12
ECE	E11-106R-007527
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64	67
45	6250	7040	7690	8080	8470	8730	9000	9520	9910	10300	10700	11080	11350	11730	12000	12520	13040	13690
From 40 to 25	6880	7740	8460	8890	9320	9610	9890	10470	10900	11330	11750	12180	12470	12900	13190	13760	14330	15220
20	7020	7900	8620	9070	9500	9790	10080	10660	11100	11550	11990	12430	12710	13150	13440	14030	14620	15520
12	7150	8050	8790	9240	9680	9980	10280	10870	11330	11780	12220	12670	12970	13410	13710	14300	14910	15830
5	7570	8510	9300	9770	10240	10560	10870	11500	11980	12450	12920	13400	13720	14190	14500	15130	15770	16740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 00:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..