

AGRIMAX TURF RT 333 - Specifiche tecniche



Description

AGRIMAX TURF RT 333 (R-3 +) è uno pneumatico radiale progettato per piccoli trattori in applicazioni di giardinaggio, in vigneti e frutteti. Il suo design arrotondato fornisce bassa compattazione del terreno e lo rende estremamente delicato sul terreno. Il suo esclusivo battistrada extra profondo (R-3 +) e il design speciale con blocchi direzionali garantiscono un'eccellente trazione sia sul campo che su strada, nonché un ciclo di vita prolungato. AGRIMAX TURF RT 333 (R-3 +) garantisce grandi proprietà di autopulizia e, grazie alla sua bassa resistenza al rotolamento, consente un notevole risparmio di carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina per il raccolto di frutteti • Trattorino
• Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	380/70 R 20
LI/SS	122 A8/122 B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1082
Static Loaded Radius (mm)	486
Rolling Circumference (mm)	3213
SRI (mm)	500
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E11-106R-007111

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	825	960	1095	1230	1365	1500
40	825	960	1095	1230	1365	1500
30	885	1030	1175	1320	1465	1605
10 LT	1110	1290	1470	1650	1830	2010
10 HT	885	1030	1175	1320	1465	1605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 04:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..