

EARTHMAX SR 331 - Specifiche tecniche



Description

EARTHMAX SR 331 è il nuovo pneumatico BKT con battistrada multiblocco appositamente progettato e disegnato per camion multiuso e veicoli di emergenza. L'esclusivo profilo del battistrada è essenziale per massimizzare il contatto con il suolo; garantisce, quindi, una maneggevolezza e un comfort eccellenti in tutte le condizioni. Questo pneumatico non direzionale presenta straordinarie proprietà autopulenti. EARTHMAX SR 331 è stato progettato da BKT per eccellere in galleggiamento e trazione, requisiti essenziali per operare efficacemente su terreni soffici, sabbiosi e fangosi. La lunga durata è assicurata dalla robustezza di carcassa e pacco cinture All Steel, che fornisce anche un'eccezionale resistenza a strappi e forature.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	24 R 21
LI/SS	176 G

Dimensions US Standard

Usa code	94067671
Ply Rating	16
Overall Width (inch)	23.9
Overall Diameter (inch)	54.4
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	165.1
Rim Rec	18.00
ECE	E11-54R-0019350
Tread Depth	30

Load capacity (lbs)

mph / psi	85
56	15700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 23:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..