

EARTHMAX SR 35 - Specifiche tecniche



Description

Earthmax SR 35 è uno pneumatico radiale All Steel a basso profilo specificamente progettato per dumper articolati e pale gommate. È ideale per operazioni che richiedono eccellente trazione e galleggiamento. Earthmax SR 35 assicura sia trazione che stabilità eccellenti. Grazie alla robusta carcassa con cinture in acciaio, lo pneumatico garantisce straordinaria durabilità oltre a resistenza contro strappi e forature.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	214 A2

Dimensions US Standard

Usa code	94059836
Overall Width (inch)	35
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	32.1
Rolling Circumference (inch)	218.9
Rim Rec	27.00/3.50
Rim Alt	27.00/3.0, 28.00/3.5
Star Rating	*
TRA Code	L3
Tread Depth	60

Load capacity (lbs)

mph / psi	58	62	65	69
5	40800	43000	45400	46700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 03:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..