

HARVESTER SPECIAL - Specifiche tecniche



Description

HARVESTER SPECIAL è stato specificatamente progettato per mietitrebbie. I ramponi a doppia angolazione assicurano trazione eccellente sul campo e un ottimo comfort di guida su strada. Lo speciale disegno del battistrada offre maggiore contatto per una straordinaria stabilità. HARVESTER SPECIAL si distingue per la carcassa robusta e una mescola particolarmente resistente a tagli e lacerazioni, assicurando un ciclo di vita più lungo dello pneumatico

UM

US Standard

Construction

BIAS

Machinery

Agricoltura: Mietitrebbia

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	155 A8

Dimensions US Standard

Usa code	94062089
Ply Rating	16
Section Width (inch)	23.1
Overall Diameter (inch)	62.4
Static Loaded Radius (inch)	28.3
Rolling Circumference (inch)	189.2
Rim Rec	DW 20 B ; DW 20 A
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	8550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 02:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..