

SKID POWER HD (A) - Specifiche tecniche

Description

SKID POWER HD (A) è stato progettato per pale skid steer nelle applicazioni dell'edilizia. Lo pneumatico si distingue per il battistrada extra profondo e la protezione dei fianchi, che assicurano eccellente resistenza a tagli e strappi nonché straordinaria durabilità. SKID POWER HD (A) è lo pneumatico ideale per superfici terrose e impieghi pesanti.



UM

US Standard

Construction

 BIAS

Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	27 X 8.50 - 15

Dimensions US Standard

Usa code	94017881
Ply Rating	8
Section Width (inch)	8.6
Overall Diameter (inch)	26.6
Static Loaded Radius (inch)	12.8
Rolling Circumference (inch)	78.9
Rim Rec	7 JA

Load capacity (lbs)

mph / psi	61
5	2890
10	2280
15	2110

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 23:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..