

## SNOW GRIP - Scheda tecnica



### Description

SNOW GRIP è stato particolarmente progettato per carrelli elevatori che operano in ambienti a basse temperature. Il disegno unico del battistrada è caratterizzato da speciali bordi che garantiscono un grip superiore su neve fresca o compatta, assicurando eccellenti performance in curva e frenata sulle superfici ghiacciate e innevate. La struttura a doppio tallone, la robusta carcassa e la particolare protezione dei fianchi si traducono in elevata capacità di carico nonché eccellenti stabilità e manovrabilità in modalità di sollevamento, garantendo inoltre un ciclo di vita prolungato dello pneumatico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Carrello elevatore

| SIZE      | Version  | LI/SS  | PR | RIM REC | RIM ALT | SW  | OD  | Type |
|-----------|----------|--------|----|---------|---------|-----|-----|------|
| 7.50 - 16 | STANDARD | 131 A2 | 12 | 6.0     |         | 210 | 810 | TT   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 08:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..