

TR 138 - Specifiche tecniche



Description

TR 138 è stato specificamente sviluppato per sollevatori telescopici e terne nell'agricoltura ed è particolarmente idoneo per la lavorazione del terreno e applicazioni di irrorazione. Ottima trazione su terreno morbido, autopulitura e stabilità sono le caratteristiche chiave che rendono TR 138 lo pneumatico ideale anche in condizioni difficili del terreno.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Terna • Sollevatore telescopico

Version	STANDARD
Type	TL
Tyre Size	17.5L - 24
LI/SS	151 A8

Dimensions US Standard

Usa code	94061877
Ply Rating	12
Section Width (inch)	17.7
Overall Diameter (inch)	50.8
Static Loaded Radius (inch)	22.7
Rolling Circumference (inch)	151
Rim Rec	DW 15L
Rim Alt	DW 14L
ECE	E11-106R-005232

Load capacity (lbs)

mph / psi	25
39	7605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 01:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..