

## MP 567 - Technical Specifications



### Description

MP 567 is an agro-industrial tire suitable for field and road transport and municipality/maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Telehandler  
Industrial: Telehandler • Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	12.5 - 18

## Dimensions US Standard

Usa code	94038138
Ply Rating	16
Section Width (inch)	12.8
Overall Diameter (inch)	39
Static Loaded Radius (inch)	17.7
Rolling Circumference (inch)	115.7
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022628

## Load capacity (lbs)

mph / psi	65
55	4960
25	5700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 20:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..