



MP 585 - Data Sheet



Description

MP 585 is an agro-industrial tire, which is suitable for multi-purpose vehicles in municipality/maintenance applications. This tire is specially engineered with a block pattern that offers maximum stability and durability in the most difficult working conditions, also at high speeds.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Universal Vehicle

Industrial: Universal Vehicle

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.5 - 20	STANDARD		10	9	9 SDC	273	970	455	2890	TL	E4-54R-0022631
12.5 - 20	STANDARD		12	11	12 SDC	335	1050	480	3130	TL	E4-54R-0022635
6.50 - 20	STANDARD	106 A6	10	5.50 F	4.00 E ; 5.00 F	200	875	0	0	TT	E11-106R-004308

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 16:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..