

MT 617 - Technical Specifications



Description

MT 617 has been specially designed for military trucks. It is a run-flat tire featuring excellent traction and high puncture resistance. Besides, its sidewall protection contributes to an extended tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Military Truck

Version	ARAMID BELTED
Type	TL
Tyre Size	14.5 - 21

Dimensions International Standard

Ply Rating	12
Section Width (mm)	392
Overall Diameter (mm)	1220
Rim Rec	10

Load capacity (Kg)

km/h / bar	4.80	4.20
90 LS	3605	-
90 LD	-	3160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 00:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..