

## PAC MASTER - Technical Specifications



### Description

PAC MASTER is a bias tire for compactors. It shows high stability and ensures an extended tire life-cycle. It is made of a special compound that provides particular heat resistance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Compactor

Version	STANDARD
Type	TL
Tyre Size	190/60 - 15

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	186
Overall Diameter (mm)	610
Static Loaded Radius (mm)	291
Rolling Circumference (mm)	1853
Rim Rec	6.0
ECE	E11-106R-005272

## Load capacity (Kg)

km/h / bar	2.80
10	750
15	600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 21:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..