

POWER TRAX HD (FL) - Technical Specifications



Description

POWER TRAX HD is a premium bias-ply tire that is specially designed for forklift equipment in industrial applications. The deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut, chip and tear resistance suitable for rough and hard concrete surface. The specially designed rim guard ensures protection against flats and wheel damages in the rim flange area.

UM

International Standard

Construction

Se BIAS

Machinery Industrial: Forklift

Version	STANDARD
Туре	тт
Tyre Size	10.00L - 15 (36 X 11 - 15)

Dimensions International Standard

Ply Rating	16
Section Width (mm)	285
Overall Diameter (mm)	918
Rim Rec	7.50 BD
Rim Alt	7.5

Load capacity (Kg)

km/h / bar	9.00
25 LOAD WHEEL	5525
25 STEER WHEEL	4250
10 OTHER VEHICLES	5525
25 OTHER VEHICLES	4250
STATIC SIDE LOADER	6420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 21:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..